

# GP-T801

## 2-Core FTTH Fiber Wall Outlet

### Application

- GP-T801 is a fiber optic customer outlet that enables simple and unobtrusive termination of fiber optic cables in offices, homes or communication rooms.
- IP20 Rated, suitable for indoor wall mount application.



### Key Features

- Dual connectivity - Supports 2 termination/splice connections (2 SC simplex adapters can be pre-installed).
- Ultra-flat profile (80\*80\*20.5mm) - Fits flush against walls or electrical outlets.
- Multi-directional cable entry - Bottom, left, and rear openings for flexible installation.
- Optimized internal routing to maintain  $\geq 30\text{mm}$  bend radius.
- Adapter stability - SC adapters can be inverted in holders to prevent accidental disconnection when cables are pulled.
- IP20 rated - Basic dust protection for indoor use (not waterproof).
- RoHS compliant (Optional) - Standard material can be upgrade to environmental friendly materials.
- Flame-retardant housing (Optional) - Standard material can be upgrade to UL 94 V-0 certified plastic.
- RAL 9010 white finish - Aesthetic and discreet for residential/office environments.
- Tool-less access - Easy-open design for quick maintenance.
- Included mounting kit - Screws and anchors for wall-mounting.

## Specifications

Part No.	GP-T801
Color	White
Dimensions	80 x 80 x 20.5mm (3.15 x 3.15 x 0.81 in)
Patching Capacity	2 SC
Splice Capacity	1/2 Fibers
IP Rating	IP20
Mounting Option	Wall Mount
Material	ABS
Environmental Space	Indoor
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

## Accessories

Picture	Name	Size	Qty
	Wall-mounting Kit	-	2 Pairs

## Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GP-T801	41*41*36CM	400	12 KG